



Specifications Ledvance LED
Downlight Alu DN150 14W 1190lm
100D - 830 Warm White | 160mm -
IP44 - Dali Dimmable

[View Product](#)

General Information

| | |
|--------------------------|-------------------------------------|
| SKU | 235457 |
| EAN | 4058075202610 |
| Brand | Ledvance |
| Manufacturer Name | DL ALU DALI DN150 14W/3000K WT IP44 |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 100 |

| | |
|--------------------------|---------------------------------------|
| Luminous Efficacy (lm/W) | 85 |
| Power factor | >0.90 |
| Installation Depth (mm) | 100 |
| Unified Glare Rating | < 28 - for hallways and storage rooms |
| Optical Cover | PMMA (Polymethyl methacrylate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|----------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | -20 to +45 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | Screwless terminal, 5-Pole |
| Series | DOWNLIGHT ALU |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 160 |
| Diameter (mm) | 160 |

Why Any-lamp?

Sensor Information

 Order from the **largest lighting specialist** in Europe  **Customised** quotation
 Type of sensor No Sensor

 **Up to 7 years warranty**  **Easy return process**